

# Modems

## for the MOSCAD RTU

### FEATURES

*The MOSCAD RTU may communicate RTU-to-central or RTU-to-RTU on wirelines when desired. A family of modem accessories is available for direct installation within the MOSCAD NEMA or RackMount RTU. Operating power for the modems is derived from the MOSCAD power source, including the backup battery.*



#### Mechanical

Each modem consists of two assemblies: the modem electronics installs within the CPU module of a no-radio MOSCAD RTU; the line interface unit installs in the space normally occupied by the radio.

◆ *The MOSCAD RackMount configuration provides additional places to install the line interface unit, so that simultaneous radio and wireline (modem) communications may be provided if needed.*

#### Electronics

Two versions of the modem electronics are available. Both provide low-speed (600 and 1200 bps) data communications, whereas one also provides mid-speed (2400 bps) data communications.

◆ *The modem electronics plugs into the CPU module in the space normally occupied by the radio interface electronics for an efficient connection to the microprocessor. The modem also operates from the MOSCAD backup battery power source.*

#### Line Interface

Three versions of the line interface units are available. These permit wireline communication systems that involve dial/answer operation through the Public Switched Telephone Network (PSTN), dedicated 2-wire or 4-wire point-to-point operation, or 2-wire point-to-multipoint (multidrop) operation.

◆ *The system manager may use the dial/answer (PSTN) capability to dial into the system for maintenance purposes. RTUs may also use this dial-in connection for their communication requirements. Three or more RTUs may be interconnected into a communications (sub)system by using point-to-multipoint (multidrop) modems.*

#### Connections

RJ-11 connectors or standard screw terminals may be used for 2-wire connections.

◆ *The RJ-11 connectors provide an easy method of connecting the modem to the telephone lines. Screw terminals are available if needed.*



**MOTOROLA**

## Specifications

<b>Order</b>	See chart below
<b>Signal Levels</b>	Wireline to Modem: -3 dBm to -47 dBm (-35 dBm for multidrop) into 600 ohms Modem to Wireline: -10 dBm into 600 ohms
<b>Power</b>	5 Vdc: 0 ma 12 Vdc: 6 ma
<b>Environment</b>	Humidity: 0 to 90% @ +50°C Temperature: -30 to +60°C

Plant Installed	Field Installed	Modem Type	Data Speed/Modulation	Standard	Interface
V104	FRN5669 Plug-in board FRN1985 Line interface	Dial/Answer (PSTN)	600 DPSK 1200 DPSK	CCITT V.22/Bell 212 CCITT V.22/Bell 212	Asynchronous Asynchronous
V226	FRN5639 Plug-in board FRN1985 Line interface	Dial/Answer (PSTN)	600 DPSK 1200 DPSK 2400 QAM	CCITT V.22 CCITT V.22/Bell 212 CCITT V.22bis	Asynchronous Asynchronous Asynchronous
V219	FRN5669 Plug-in board FRN1986 Line interface	Multidrop (point-to-multipoint) half-duplex	600 DPSK 1200 DPSK	Proprietary (MDLC) Proprietary (MDLC)	Synchronous Synchronous
V285	FRN5669 Plug-in board FRN1987 Line interface	Leased wireline (point-to-point) full duplex	300 FSK 600 DPSK 1200 DPSK	CCITT V.21/Bell 103 CCITT V.22 CCITT V.22/Bell 212	Sync/Asynchronous Sync/Asynchronous
V404	FRN5639 Plug-in board FRN1987 Line interface	Leased wireline (point-to-point) full duplex	300 FSK 600 DPSK 1200 DPSK 2400 QAM	CCITT V.21/Bell 103 CCITT V.22 CCITT V.22/Bell 212 CCITT V.22bis	Sync/Asynchronous Sync/Asynchronous Sync/Asynchronous



### Support Services

Wherever Motorola sells, our product is backed by service. Our products are serviced throughout the world by a wide network of company or authorized independent distributor service organizations. Specifications subject to change without notice.



**MOTOROLA**

1301 E. Algonquin Road  
Schaumburg, Illinois 60196  
In the U.S. call: 1-800-247-2346  
Outside the U.S. call: (708) 576-3107

® and Motorola are trademarks of Motorola, Inc. © 1994  
Motorola, Inc. Printed in U.S.A. Produced  
by Customer Communications. 36 USC 380  
Motorola is an Equal Employment Opportunity/  
Affirmative Action Employer